

Note: This data sheet is for informational purposes. It is not a commitment to deliver hardware features or functionality. The development, release and timing of features and functionality described in this document are at the sole discretion of Five9 Network Systems.

FIVE9NS T3205 TOWER SERVER



The Five9NS T3205 is dual socket, quad-core or six-core, tower server. Powered by Intel Xeon E5-2600 series processors, this versatile system provides I/O slot flexibility that enables seamless integration into a variety of OEM applications.

HIGHLIGHTS:

- 5 PCIe slots + dedicated RAID slot
- Tower form factor
- Dual 10GbE ports + Dual 1 GbE ports
- Supports Windows, Linux and Solaris Operating Systems
- Remote system management capabilities ideal for central office and other demanding environments
- Easy to customize and integrate into existing infrastructure
- Easy to scale out as business needs grow



Flexible Tower Server

The Five9NS T3205 was designed with OEM needs in mind. With its rich feature set – including 6 expansion slots, remote management capabilities, and high performance Intel E5-2600 series processors it's an ideal fit for commercial printing and healthcare environments.

Specialty Services

OEM customers can choose from a host of services that will accelerate the integration process and reduce time to market.

With our in-house Product Lifecycle Management service, Five9NS is uniquely positioned to architect systems for OEM customers. The Five9NS T3205 tower server is customizable and you can brand it as your own. We also provide free engineering support via experts who understand the unique requirements of OEM customers.

The Five9NS Product Lifecycle Management service aims to help you proactively manage your product lifecycle. We'll implement a product lifecycle matched to your needs, providing up to a 5-year product life from the date of contract, which can be extended upon request.

Note: This data sheet is for informational purposes. It is not a commitment to deliver hardware features or functionality. The development, release and timing of features and functionality described in this document are at the sole discretion of Five9 Network Systems.

FIVE9NS T3205 TOWER SERVER

FEATURES	PLATFORM
Form Factor	Tower (22" x 16.9" x 8.7")
Processors	2 x Intel Xeon E5-2600 series
Processor Sockets	Two (FC-LGA 2011)
Chipset	Intel C602-A PCH
Memory	16 sockets, supports DDR3-1600 ECC LRDIMMs, RDIMMs and UDIMMs, up to 512GB maximum
I/O Slots	1 PCIe Gen3 x 16, Full Height – Half Length 2 PCIe Gen3 x 16, Full Height – Full Length 1 PCIe Gen3 x 8, Full Height – Full Length 1 PCIe Gen2 x 4, Full Height – Full Length 1 Dedicated RAID Slot
SATA Software RAID	Intel RSTe (for Windows only), RAID 0/1/10/5 LSI MegaRAID driver supports software RAID 0/1/10 (Windows and Linux)
Optional SAS/SATA RAID	LSI RAID adapters
Drive Bays	4 x 3.5" Hot Swap or 6X 2.5" Hot Swap
Hard Drives (Fixed or Hot Swap)	Enterprise Class 3.5 inch SAS (15K rpm) Enterprise Class 2.5 inch SAS (15K rpm) Enterprise Class 2.5 inch SAS (10K rpm) Nearline 2.5 inch SATA (7.2K rpm) Nearline 2.5 inch SAS (7.2K rpm) Nearline 3.5 inch SAS (7.2K rpm) Nearline 3.5 inch SATA (7.2K rpm)
Optical Drive	DVD-Multiwriter
Network Interface	2 x 10GbE ports (SFP+) + 2 x GbE ports + GbE IPMI port
Serial Ports	1 (DB9) + optional 2 nd port
USB Ports	7 ports (4 rear, 2 front, 1 internal Type A)
Power Supply	Single 600W or Redundant 820W
Video	DB15 on rear panel (16MB)
Management Hardware	Integrated IPMI 2.0 BMC, Remote Management Module
OS Support	Solaris, Linux, Windows